

# DS-TMG300-D/A 30 Series Straight Pole Barrier Gate with Strip Light



- Supports convenient side installation with compact structure.
- Adopts small DC brushless motor with low noise to increase output torque and realize precise intelligent control.
- Supports multiple anti-fall modes such as IR, vehicle detectors, and radars.
- Delayed boom pole closing. Supports 1 to 99 seconds.
- Intergated with strip light to show barrier gate status.



## Specification

Barrier Housing		
Barrier Housing Material	Cold-rolled sheet	
Barrier Housing Thickness	1.2 mm	
Barrier Housing Door Thickness	1.0 mm	
Barrier Housing Color	Black background with sliver pattern	
Barrier Housing Door Color	Black background with sliver pattern	
Boom Pole Installation Height	880 mm	
Body Indicators	None	
Barrier Gate General		
Boom Pole Direction	Left/Right	
Motor Type	DC brushless motor	
Matched Boom Pole Type	Boom pole with strip light	
Rising/Falling Speed	3 to 6 s	
Boom Pole Falling Delay	1 to 99 s	
Number of Cycles	5,000,000	
Working Voltage	24 VDC	
Consumption	100 W	
Temperature and Humidity	Humidity: ≤ 90	
Rising Boom Pole for Poweroff	Optional	
Package		
Barrier Housing Dimensions (L ×	225 220 4000 /4.05 0.72 2.20; 1)	
W×H)	$325 \times 220 \times 1000 \text{ mm} (1.06 \times 0.72 \times 3.28 \text{ inch})$	
Body Weight	26 ± 0.2 kg (57.32 ± 0.44 lb.)	
Body Dimensions (with Package,	205 v 205 v 4060 mm /4 26 v 4 v 2 40 im -h	
Without Boom Pole) (L $\times$ W $\times$ H)	$385 \times 305 \times 1060 \text{ mm } (1.26 \times 1 \times 3.48 \text{ inch})$	
Body Weight (with Package,	20.1 ± 0.2 kg (64.15 ± 0.44 lb.)	
Without Boom Pole)	29.1 ± 0.2 kg (64.15 ± 0.44 lb.)	
Interface		
RS-485	Optional	
Rising to Limit	1 group	
Falling to Limit	1 group	
Open	1 group	
Close	1 group	
Stop	1 group	
IR/Vehicle Detector/Radar	1 group	
Traffic Signal Light	1 group	
Approval		
Protection	IP54	
Boom Pole		
Boom Pole Color	White background with red bar	
Boom Pole Weight	3 m boom pole with strip light : $3.5 \pm 0.2$ kg 4 m boom pole with strip light : $4.5 \pm 0.2$ kg	
	Para	



Boom Pole Dimensions (with Package)	3 m boom pole with strip light : $3050 \times 100 \times 55$ mm
	4 m boom pole with strip light : $4050 \times 100 \times 55$ mm
Boom Pole Weight (with	3 m boom pole with strip light : 4.1 ± 0.2 kg
Package)	4 m boom pole with strip light : $5.3 \pm 0.2 \text{ kg}$
Boom Pole Dimensions	X × 50 × 95 mm
Boom Pole Material	6063

### Available Model

DS-TMG300-DL/A(3m strip light)

DS-TMG300-DR/A(3m strip light)

DS-TMG300-DL/A(4m strip light)


DS-TMG300-DR/A(4m strip light )

DS-TMG300-DL/A(6m strip light)

DS-TMG300-DR/A(6m strip light)



### Dimension



Unit: mm

Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 www.hikvision.com

Follow us on social media to get the latest product and solution information.





HikvisionHQ



HikvisionHQ





