Φ300mm LED Traffic Light R/A/G(with 2-color countdown timer)

Model No.: JD300-3-FM31 Type04



Connection Sketch

Black: Common red: red light

yellow: yellow light green: green light

Product Photo



Product Features

- Novel design with beautiful appearance
- Low power consumption
- High efficiency and brightness
- Large viewing angle
- Long lifespan-more than 80,000 hours
- Multi-layer sealed and waterproof
- Exclusive optical lens and good color uniformity
- Long viewing distance
- Keep up with CE, GB14887-2007

Technical Parameters:

Color	LED	Light	Wave	Viewing angle		Dawer	Working	Housing	
Color	Qty	Intensity(cd)	length	L/ R	U/D	Power	Voltage	Material	
Red ball	168pcs	≥600cd	625±5nm	30°	30°	≤10W		PC UV resistant	
Yellow ball	170pcs	≥800cd	590±5nm	30°	30°	≤10W			
Green ball	168pcs	≥800cd	505±5nm	30°	30°	≤10W	85V-265VAC,		
Red count down		≥15000cd/m ²	625±5nm	30°	30°	≤8W	50/60HZ		
Green count down	64pcs	≥35000cd/m²	505±5nm	30°	30°	≤10W			

Packing Info. :

Carton size	QTY	GW	NW	Wrapper	Volume(m³)	
1.22*0.42*0.31 m	1pcs/carton	12.5 KGS	10.52 KGS	K=K Carton	0.114	

Packing List :

Installation Sketch

Name	Light	L Bracket	Sun visor	M4×10 Screw	M4×10 Screw and Nut with Gasket	M4× 20 Screw	Wiring Box and Gasket	Fastener	Manual and Certific ate
Qty.(pcs)	1	2	3	32	4	4	1	4	1

588 4-Φ16.0通孔-Φ25.0单边孔₇ d 尺寸(size) d1 1050 d2 1200 d3 1360 Ϊ 1300 单位unit:mm d2 H 右视图 (2) right view(2) 右视图 (3) right view(3) 主视图 右视图(1) 后视图 灯杆钻孔图 Elevation right view(1) back view Light pole Installation Holes Chart (with decorative sheet)