



28AWG REDUCED DIAMETER CAT 6 CHANNEL CORD, BLUE, 5'

OR-RDC605-06 | Ortronics

FEATURES & BENEFITS

RDC 6 Modular Patch Cord, blue, 5', reduced diameter, 28 AWG, cat6 channel four-pair UTP stranded PVC/CM.





- Each cord is factory tested: Ensures every cord shipped meets Category 6 channel specifications.
- Reduced diameter mini patch cord : takes up less cable management space and leaves mores space for airflow
- Premium plug designed for reduced OD 28 awg patch cable: Protects performance integrity through the plug termination .
- $\bullet \ \textbf{Snagless plug design:} \ \textbf{Protects plugs when pulling through cable managers or pathways} \ . \\$
- Premium 28 awg conductor cordage: Reliable performance and durable cord life.
- Compatible with both T568A and T568B wiring: Provides universal wiring ability.
- Backwards compatible to Category 3, 5, and 5e: Supports lower category installations and components.

SPECIFICATIONS

GENERAL INFO

Cable Type: Four-pair 28 awg stranded UTP CMR rated

Color Cable Jacket: Blue

Pair Count: 4 pair

Performance Category: Cat 6 component compliant

Termination: 8-Position Modular plug

Typical Applications: IEEE 802.3 1000Base-T (Gigabit Ethernet), 10-100Base-T, TIA/EIA-854 1000Base-TX, ATM

CB1G

Type: Patch Cord

LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

RoHS: Yes

FCC Standard: Yes

CONSTRUCTION INFORMATION

Component 1: Cable

Component 2: Eight-position plug assembly Component 3: Modular plug IDC contacts Component 4: Clear plastic strain relief

Material 1: 28 AWG tinned copper stranded conductors, HDPE insulation, PVC jacket

Material 2: Polycarbonate plug housing and conductor centering sled

Material 3: Phosphor-bronze contacts designed for smaller 28awg conductors

Material 4: Molded PolyCarbonate

DIMENSIONS

Diameter (Metric): 3.94 mm Diameter (US): 0.155" Length (Metric): 1.52 m

CORD INFORMATION

Connector Type End One: Plug, HSG, eight-contact, RJ45, C6 performance Connector Type End Two: Plug, HSG, eight-contact, RJ45, C6 performance

Jacket Rating: CMR Cord Length Metric: 1.52 m

Cord Length US: 5'

Pinning: Straight 1-1, 2-2, 3-3, etc.

TECHNICAL INFORMATION

Category Rating: Cat 6 OhmValue: 100 Ohm Performance Rating: Cat6 Wire Gauge: 28 AWG

BUY AMERICAN ACT COMPLIANCE

Country Of Origin: MEXICO

Buy American Act Status: Trade Agreement Act Compliant

